

NEW

ASSET GUARD

ECO

LTE-M (Cat-M1)/NB-IoT

Lowest-cost battery-powered indoor/outdoor asset tracker for LTE-M/NB-IoT networks



149 x 51 x 21 mm (5.9 x 2 x 0.8 in)

📍 Indoor/Outdoor

GNSS, Wi-Fi AP MAC Address Scanning, and Cell Tower location for seamless indoor/outdoor asset management

🔋 'Deploy Once' Battery Life

10+ years on 2 x AA user-replaceable batteries with 'Battery Low' and 'Battery Critical' alerts

☁️ Cloud-Based Location

Position calculations are handled in the cloud (versus on-device) for substantial power savings

➡️ Adaptive Tracking

Tracks assets when they're on the move and enters sleep mode when stationary to conserve energy

🔔 Magnetic Activation & Tamper Detection

Magnetic switch for activation and Tamper Detection

Slim & Ultra-Rugged

Compact and waterproof housing ensures the device can withstand impact, fine dust, and brief submersion

Connectivity

	Nordic nRF9160 Modem operates on all major global LTE-M and NB-IoT bands
Cellular Module	Supported LTE bands: LTE-M (Cat-M1): B1, B2, B3, B4, B5, B8, B12, B13, B14, B17, B18, B19, B20, B25, B26, B28, B66 NB-IoT (Cat-NB1/NB2): B1, B2, B3, B4, B5, B8, B12, B13, B17, B19, B20, B25, B26, B28, B66
SIM Size & Access	Internal Nano 4FF SIM (Included)

Location

Chipset	Semtech LR1110
Environment	Indoor/Outdoor
GNSS Scanning	Concurrent GPS/BeiDou
Wi-Fi Location Scanning	Indoor asset location using Wi-Fi access point scanning
Cell Tower Location	Cell tower fallback for positioning when there is no GNSS or Wi-Fi signal
Cloud-Based Solver	Asset location is calculated using cloud based localisation.
*Location Accuracy	~5m-80m with GNSS scanning in open areas
	~10m-100m with Wi-Fi in urban areas
	~250m-1km Cell Tower Geolocation - dependent on number of nearby towers
	Results vary depending on real world conditions
Low Noise Amplifier	GPS signals are filtered and boosted by a SAW filter and low-noise amplifier (LNA) allowing operation where other units fail
GNSS Assistance	GNSS almanac data for greater sensitivity and position accuracy

*Results vary based on real world conditions. Device configuration, installation, environmental conditions, augmentation services, and many other factors may lead to variations in positioning accuracy.

Power

Input Voltage	2.2 - 3.6V
Sleep Current	<10uA* *Average current in lowest power configuration

Batteries

User-Replaceable Batteries	2 x AA. Batteries not included.
Supported Battery Types	Alkaline Lithium (LiFeS2) – recommended for best performance *Please dispose of Lithium batteries in a safe and responsible manner
*Battery Life Estimates	Once Daily location updates – 10 years **Movement-Based location updates – 5 years Hourly location updates – 3 years

* Battery life estimates are influenced by several factors including temperature, installation and orientation of the device, the frequency of location updates, network coverage, sensor integrations, peripherals, accelerometer settings, and more. Battery life calculators are available.

** Movement-based estimates are based on 2 hours of movement, occurring 5 days a week, with default tracking parameters (location updates every 3 minutes and uploads every 30 minutes). Devices can be configured to provide more frequent location updates when the asset is in motion.

Mechanics/Design

Dimensions	149 x 51 x 21 mm (5.9 x 2 x 0.8 in)
Housing	Rigid plastic
IP/IK Rating	Ultra-rugged and waterproof IP68 and IK07-rated housing ensures the AssetGuard Eco can withstand impact, fine dust, and brief submersion
Installation	Compact and concealable. Multiple installation options for covertly and easily securing the device to assets with screws, bolts, cable ties, rivets, and more.
Magnetic Switch	Magnetic switch enables quick activation and tamper detection
Operating Temperature	-30°C to +60°C
Cellular Antenna	Internal
GPS Antenna	Internal
Wi-Fi Antenna	Internal
3-Axis Accelerometer	3-Axis accelerometer to detect Movement and High-G events
Diagnostic LED	Diagnostic LED indicates operation status
Flash Memory	Internal flash memory stores approximately 1400 records if device is out of cellular coverage
Speed and Heading	Scanning technology used on the AssetGuard Eco does not return speed and heading
Onboard Temperature	The device reports internal temperature which provides an indication of ambient temperature

Smarts

Adaptive Tracking	Configure parameters to send updates based on set time intervals or when movement occurs. Adaptive tracking technology detects when the device is on the move and increases the update rate, providing detail when you need it while conserving battery when stationary.
Battery Life Monitoring	‘Battery Low’ and ‘Battery Critical’ alert levels
Geofence Alerts	The server can use device location to create geofences and alerts if an asset enters or leaves designated locations
Impact Detection	Configure impact-detection alerts when G-forces are exceeded by a user-defined threshold
Magnetic Activation	Magnetic switch can be used to activate the unit – meaning SIM cards and batteries can be pre-installed, simplifying deployment
Rotation Counting	Keeps a count of the number of rotations of the device about the Z axis
Run Hour	Capture run hours based on movement to understand and optimize asset utilization
Monitoring Sleep Mode	Stationary devices enter sleep mode until movement occurs to conserve battery life and optimize data usage
Tamper	Magnetic switch provides an alert if the device is removed from your asset
Detection Theft	Switch to Recovery Mode in the case of theft or loss to activate real-time tracking for asset
Recovery	Retrieval
Tip Detection	Define a range of angles that constitutes a ‘tipped’ state and configure alerts

Device Management

Flexible Configuration	Configure device parameters such as position update rate, movement, and accelerometer settings, and more to fit any tracking application
Device Management Platform	Manage, monitor, configure, debug, update, and restart devices remotely from our cloud-based device management system
Configuration App	Configurable with DM-Link provisioning tool

Security

Data Security	Military-level AES-256 Encryption from device to Device Manager to protect the integrity and confidentiality of telematics data. Data forwarded to third-party systems is sent via HTTPS for end-to-end security.
---------------	---

Warranty

Manufacturer’s Warranty	Two-year manufacturer’s warranty.
-------------------------	-----------------------------------

Certifications

Please enquire for certifications.
